

DiBo – 13.0 TECHNICAL DATA SHEET

INDOKON Dimple Drain board is specifically designed for use with all waterproofing membrane systems as well as any torch-applied waterproofing membranes surface. It is made of high density polyethylene (HDPE). It is light weight, flexible, strong, durable, non-toxic, dimple sheet board with 13.0 mm deep dimples. It is impermeable to water and water vapour.

It is an efficient, filtered sub-soil drainage system used for drainage of all in- ground structures. It comprises a highly compression resistant and flexible studded plastic dimple core.

DIMPLE BOARD PROPERTIES

Properties	Unit	Value
Drainage Core		HDPE
Thickness @ 2 kPa [EN ISO 9863-1]	mm	13.0 [$\pm 10\%$]
Compressive Strength [ASTM D1621]	kPa	>150
Sheet Thickness	mm	0.50
Hydraulic Properties		
In Plane Water Flow $i=1.0$ @ 100 kPa [EN ISO 12958]	l/m.s	5.0
Product Dimensions		
Roll Width	m	2.30
Roll Length	m	20.00

Notes

- Reported value are arithmetic mean values unless otherwise stated, A set of test results derived from specimens cut from one sample and taken across full width of the roll.
- The above properties might change at the time of the manufacturing, storing, handling or shipping.
- There may be variation in above values due to various factors when tested at other laboratory.
- For any queries / sale inquiries , email us on sales@indokon.in

Mo: +91 9830466099 | +91 9903021313

E: sales@indokon.in

W.: www.indokon.in